

Barbed Fittings

小接头

RTU



Straight Connector for Air Tubing
 Assembly: Slide on the hose to the stop. Disassembly: cut open the hose.

Item Code	Tube ID 1-mm	Tube ID 2-mm
RTU2/2	2	2
RTU3/2	3	2
RTU3/3	3	3
RTU4/3	4	3
RTU4/4	4	4
RTU6/4	6	4
RTU6/6	6	6

TPK



T-connector for Air Tubing
 Materials: brass and plastic
 Temperature range: -10 °C to max. +60 °C

Assembly: Slide on the hose to the stop. Disassembly: cut open the hose

Item Code	Tube ID-mm
TPK 300	3
TPK 400	4
TPK 600	6

LPK



L-connector for Air Tubing
 Materials: brass and plastic
 Temperature range: -10 °C to max. +60 °C

Assembly: Slide on the hose to the stop. Disassembly: cut open the hose

Item Code	Tube ID-mm
LPK 300	3
LPK 400	4
LPK 600	6

YPK



Y-connector for Air Tubing
 Materials: brass and plastic
 Temperature range: -10 °C to max. +60 °C

Assembly: Slide on the hose to the stop. Disassembly: cut open the hose

Item Code	Tube ID-mm
YPK 300	3
YPK 400	4
YPK 600	6

VPK



V-connector for Air Tubing
 Materials: brass and plastic
 Temperature range: -10 °C to max. +60 °C

Assembly: Slide on the hose to the stop. Disassembly: cut open the hose

Item Code	Tube ID-mm
VPK 300	3
VPK 400	4
VPK 600	6